

PYF COMPOSITE HYDRAULIC CONE CRUSHER

PYF复合液压圆锥破碎机



设备简介

Introduction

应用范围: 用于制砂, 还可广泛应用于金属矿山、水泥厂、建材行业等

物料: 用于中、细碎抗压强度低于300Mpa硬度的各种矿石和岩石, 如铁矿石、有色金属矿石、玄武岩、花岗岩、石灰岩、石英岩、沙岩、鹅卵石等;

产品简介: 复合圆锥式破碎机, 是圆锥破碎机中的拥有弹簧和液压缸的综合型圆锥破碎机, 破碎力大、效率高、处理量高、运作成本低。力度均匀, 使用寿命长。过载保护, 有液压/弹簧保险系统, 安全高效。腔型多, 用户可根据不同的需要选择。

Applications: For sand making, it can also be widely used in metal mines, cement plants, building materials industries, etc.

Material: used for medium and fine crushing of various ores and rocks with compressive strength below 300Mpa, such as iron ore, non-ferrous metal ore, basalt, granite, limestone, quartzite, sandstone, pebbles, etc.;

Product introduction: The compound cone crusher is a comprehensive cone crusher with spring and hydraulic cylinder in the cone crusher. It has large crushing force, high efficiency, high processing capacity and low operating cost. Uniform force and long service life. Overload protection, hydraulic / spring safety system, safe and efficient.

产品参数

Main Specification

规格 Type	型号 Model	腔型 Chamber Type	破碎锥直径 Mantle Diameter (mm)	排料口调整范围 Adjusting Range of Discharge Opening (mm)	最大给料尺寸 Max Feed Size (mm)	处理能力 Capacity (t/h)	主电机功率 Main Motor Power (kw)	重量 Weight (kg)	外型尺寸 Overall dimensions (L×W×H)(mm)
Φ900	PYFB-0910	标准细型 Standard Fine Type	900	9-22	85	45-91	75	12367	2700×2275×2115
	PYFB-0917	标准粗型 Standard Coarse Type		13-38	150	59-163		12221	
	PYFB-0918	标准特粗型 Standard Super Coarse Type		25-38	150	118-163		12220	
	PYFD-0904	短头细型 Short Head Fine Type		3-13	35	27-90		13164	
	PYFD-0906	短头中型 Short Head Medium Type		3-16	51	27-100		13321	
	PYFD-0907	短头粗型 Short Head Coarse Type		6-19	65	59-129		13316	
Φ1300	PYFB-1313	标准细型 Standard Fine Type	1295	13-31	115	109-181	160	22476	2983×1866×3156
	PYFB-1321	标准中型 Standard Medium Type		16-38	178	132-253		22167	
	PYFB-1324	标准粗型 Standard Coarse Type		19-51	205	172-349		22120	
	PYFB-1325	标准特粗型 Standard Super Coarse Type		25-51	220	236-358		22125	
	PYFD-1306	短头细型 Short Head Fine Type		3-16	54	36-163		21703	
	PYFD-1308	短头中型 Short Head Medium Type		6-16	78	82-163		21675	
	PYFD-1310	短头粗型 Short Head Coarse Type		8-25	89	109-227		21789	
	PYFD-1313	短头特粗型 Short Head Super Coarse Type		16-25	113	209-236		21821	
Φ1600	PYFBII-1620	标准细型 Standard Fine Type	1676	16-38	178	181-327	250	41460	3900×2930×3242
	PYFBII-1624	标准中型 Standard Medium Type		22-51	205	258-417		41087	
	PYFBII-1626	标准粗型 Standard Coarse Type		25-64	228	299-635		40834	
	PYFBII-1636	标准特粗型 Standard Super Coarse Type		38-64	313	431-630		40674	
	PYFDII-1607	短头细型 Short Head Fine Type		5-13	60	90-209		40734	
	PYFDII-1608	短头中型 Short Head Medium Type		6-19	76	136-281		40614	
	PYFDII-1613	短头粗型 Short Head Coarse Type		10-25	113	190-336		40531	
	PYFDII-1614	短头特粗型 Short Head Super Coarse Type		13-25	129	253-336		40374	
Φ2100	PYFBII-2127	标准细型 Standard Fine Type	2134	19-38	236	544-1034	400		4613×3302×4638
	PYFBII-2133	标准中型 Standard Medium Type		25-51	284	862-1424			
	PYFBII-2136	标准粗型 Standard Coarse Type		31-64	314	1125-1814		86730	
	PYFBII-2146	标准特粗型 Standard Super Coarse Type		38-64	391	1252-1941			
	PYFDII-2110	短头细型 Short Head Fine Type		5-16	89	218-463			
	PYFDII-2113	短头中型 Short Head Medium Type		10-19	113	404-580			
	PYFDII-2117	短头粗型 Short Head Coarse Type		13-25	151	517-680		89500	
	PYFDII-2120	短头特粗型 Short Head Super Coarse Type		16-25	172	580-744			

注: 规格型号如有变动, 恕不另行通知。
Note: Specifications and models are subject to change without notice.